

VL Series[™]

»» Above-Ground Sand Filter Systems

PERFORMANCE-MATCHED PUMP AND FILTER FOR MAXIMUM ENERGY SAVINGS



VL SERIES™ SYSTEM FEATURES

- » 115V, 60 Hz pump is performance-matched to the filter for quiet operation and maximum energy efficiency
- » Clear strainer cover lets you see when the basket needs cleaning
- » High-efficiency underdrain with self-cleaning slotted laterals creates balanced flow during filtration and backwashing
- » Pump strainer basket helps prevent impeller clogs
- » No. 20 silica sand filter extends time between backwashing, creating superior water clarity with less maintenance
- » Corrosion-proof molded thermoplastic material ensures all-weather durability



VL 40 ADDITIONAL FEATURES

- » 4-position top-mount valve with two-piece flange clamp fastener creates powerful flow at low pressure
- » 11/4" and 11/2" hose adapters make installation anywhere quick and precise
- » 13" filter and 30 GPM pump



VL 210 ADDITIONAL FEATURES

- » 7-position VariFlo® valve with two-piece flange clamp fastener provides maximum flow at low pressure
- » 11/2" hose package includes two 11/2" x 6' hoses, hose adapters and hose clamps for quick and easy installation
- » 21" filter and 1.5 HP pump

SPECIFICATIONS

Model Number	VL40T32	VL210T1285S and VL210T1285STL*
Filter Type	No. 20 silica sand (.45 mm – .55 mm)	No. 20 silica sand (.45 mm – .55 mm)
Filter Tank with Integrated Pump Base	Molded polymeric	Molded polymeric
Underdrain	Unitized underdrain assembly	Unitized underdrain assembly
Control Valve	4-position, top-mount valve with lever-action handle	7-position, top-mount VariFlo® valve with lever-action handle (SP0714T)
Valve Fastening	Flange clamp design	Flange clamp design
Pump and Motor	30 GPM pump – 115 volts	1.5 HP pump – 115 volts
Mounting Base	Integrated pump base	1-piece deluxe base

^{*}VL210T1285STL includes 3' twist-lock cord

» hayward.com » 1-888-HAYWARD

VL Series Systems (TL models only) are listed by:



